HS-4-C

Diese manuelle Tisch-Patchmaschine HS-4-C ist beispielsweise für das Anbringen von RFID-Tags, Emblemen und Textiltransfers entworfen worden. Die Maschine verfügt über ein leistungsfähiges Heizelement. Die Oberplatte erwärmt sich in Sekunden. Über die digitalen Steuertasten werden Zeit, Temperaturen und der Energiesparmodus eingestellt. Die HS-4-C öffnet nach Abschluss eines Patchvorgangs automatisch, was die Arbeit erheblich beschleunigt.

Die mittleren Platten können leicht und ohne den Einsatz besonderer Werkzeuge durch kleinere ersetzt werden.

HS-4C	
Power supply (Volt)	230
Power (Watt)	600
Operating temperature (°C)	204
Temperature range (°C)	20 – 230
Press time range	1 – 60 sec.
Sealing platen (Millimeters)	125 x 95
Machine height, open	550 mm
Machine height, closed	240 mm
Machine width	550 mm
Machine depth, open	350 mm
Machine depth, closed	350 mm
Net weight (Kilogram)	21
Gross weight, including packaging (Kilogram)	23
Fuses 2x	3.15 Ampere
Weighted sound pressure (A)	<70 dB

Certification	CE