Pflegeetiketten

Pflegeetiketten (care labels) von Thermopatch sind in folgenden Varianten erhältlich:

Care Label 1 – Nylon-Taft
Ein starkes und flexibles Pflegeetikett, das auf beiden Seiten bedruckt werden kann. Mit dem modernen HiQ-MACH4.3 Drucker von Thermopatch werden Waschanweisungen und andere Informationen einfach und vor allem scharf auf das Etikett in 300 dpi gedruckt.

Care Label 3 – Extra starker Taft
Dieses schwerere Pflegeetikett eignet sich besonders für Arbeitskleidung und andere Textilien, bei denen eine industrielle Reinigung erforderlich ist. Denken Sie an Overalls, Vorhänge und sogar Pferdedecken! Diese Art von Pflegeetikett bietet auch eine Lösung für chemische Reiniger. Nach häufigem Waschen behält ein Pflegeetikett Typ 3 seinen hochwertigen Druck. Ein Pflegeetikett vom Typ 3 kann einseitig mit der Kombination aus einem Thermopatch HiQ-Drucker und einem G7-Farbband bedruckt werden.

Pflegeetiketten sind in den Breiten 30, 40 und 50 Millimeter auf einer Rolle von 100 Metern (mit einem Kern von 50 mm) in Weiß erhältlich. Andere Breiten und/oder Farben sind abhängig von der Menge auf Anfrage möglich.

Carelabel tapes

Description

- CL-01: optical white polyamide taffeta, non-fray. Both sides coated. Suitable for hotfoil, flexo and thermal transfer printing on both sides, tear resistant
- CL-01 FR: optical white polyamide taffeta, non-fray. Both sides coated. Suitable for hotfoil, flexo and thermal transfer printing on both sides, tear resistant and with additional flame retardant properties
- CL-03: extra durable polyester cotton with a thermal transfer printable topcoat from polyurethane, non-fray, tear resistant

Application

Sewable labels, safety belt labels, identification labels with barcodes.
Print with suitable inks to obtain an acceptable washability.

Properties

- CL-01 and CL-01 FR: wash: 60 °C domestic
    - Dry cleaning: yes
- CL-03: wash: 90 °C domestic

    - Dry cleaning: yes
- Additional FR properties for CL-01 FR: Flame retardant, cf US standard FMVSS 302 and Japanese standard JISD 1201. Aviation authority CAA no. 8 issue 2.

Limitations of use

None, when washing instructions of the underlying textile are followed.

Physical properties

- Fabric: polyester or polyamide taffeta, non fray, 76 g/m² for CL-01
- Fabric: polyester cotton, 100 g/m² for CL-03
- Colour: White
- For CL-03 an additional thermal transfer printable layer of white polyurethane is added onto the polyester cotton textile.

Before sealing

N/A

Heat seal advice

N/A

Storage and shelf life

The shelf life of this product is advised to be best before 12 months in original packing, in optimal storage.
Store at 18 – 23 °C, 50-55% RH, avoid UV exposure, store away from direct sunlight.

Health and safety precautions

No specific safety measures are required when working with this product.

Exposure controls / personal protection

Technical measures: N/A

Hazards identification

The product has not been subjected to classification following the European legislation. Special hazardsdesignation for humans and environment: Not applicable.

Disclaimer

This information is based on the current state of our knowledge. It is however, no guarantee of

product features and no contractual relationship.

Recommended restrictions apply

This product should not be used for purposes other than specified.

Application

This data sheet has been issued by the quality control department.