Bevarrható ruhacímke

A Thermopatch bevarrható ruhacímkék a következő változatokban érhetők el:

Care label 1 – Nylon Taft
Tartós és rugalmas bevarrható ruhacímke, melynek mindkét oldalára nyomtathat. A Thermopatch új HiQ-MACH4.3 nyomtatójával, mosási útmutató és egyéb információk nyomtathatók, rendkívül éles 300 dpi felbontásban.

Care Label 3 – Extra kemény taft
Ez, a robosztus bevarrható ruhacímke kifejezetten munkaruhákhoz alkalmazható, illetve olyan textíliáknál, amelyeket ipari mosással tisztítanak. Overállokhoz, függönyökre, vagy akár lópokrócokra. Ez a címke vegytisztítóknak is megoldást kínál. A Care label 3 Gyakori mosást követően is megőrzi a rányomtatott kiváló minőségű feliratot. A 3-as típusú bevarrható ruhacímkének az egyik oldalára nyomtathat a Thermopatch HiQ nyomtatójával és G7 festékszalagjával.

A bevarrható ruhacímke fehér színben rendelhető 30, 40 és 50 milliméteres szélességű 100 méteres tekercsekben (belső átmérő 50 mm). Egyéb méret és / vagy szín a rendelési mennyiség függvényében elérhető.

Carelabel tapes

Description

- CL-01: optical white polyamide taffeta, non-fray. Both sides coated. Suitable for hotfoil, flexo and thermal transfer printing on both sides, tear resistant
- CL-01 FR: optical white polyamide taffeta, non-fray. Both sides coated. Suitable for hotfoil, flexo and thermal transfer printing on both sides, tear resistant and with additional flame retardant properties
- CL-03: extra durable polyester cotton with a thermal transfer printable topcoat from polyurethane, non-fray, tear resistant

Application

Sewable labels, safety belt labels, identification labels with barcodes.
Print with suitable inks to obtain an acceptable washability.

Properties

- CL-01 and CL-01 FR: wash: 60 °C domestic
    - Dry cleaning: yes
- CL-03: wash: 90 °C domestic
    - Dry cleaning: yes

- Additional FR properties for CL-01 FR: Flame retardant, cf US standard FMVSS 302 and Japanese standard JISD 1201. Aviation authority CAA no. 8 issue 2.

Limitations of use

None, when washing instructions of the underlying textile are followed.

Physical properties

- Fabric: polyester or polyamide taffeta, non fray, 76 g/m² for CL-01
- Fabric: polyester cotton, 100 g/m² for CL-03
- Colour: White
- For CL-03 an additional thermal transfer printable layer of white polyurethane is added onto the polyester cotton textile.

Before sealing

N/A

Heat seal advice

N/A

Storage and shelf life

The shelf life of this product is advised to be best before 12 months in original packing, in optimal storage.
Store at 18 – 23 °C, 50-55% RH, avoid UV exposure, store away from direct sunlight.

Health and safety precautions

No specific safety measures are required when working with this product.

Exposure controls / personal protection

Technical measures: N/A

Hazards identification

The product has not been subjected to classification following the European legislation. Special hazardsdesignation for humans and environment: Not applicable.

Disclaimer

This information is based on the current state of our knowledge. It is however, no guarantee of product features and no contractual relationship.

Recommended restrictions apply

This product should not be used for purposes other than specified.

Application

This data sheet has been issued by the quality control department.