

Care Labels

Etykiety pielęgnacyjne firmy Thermopatch są dostępne w następujących wariantach:

Care Label 1 - Nylon-tafta

Mocne i giętkie wszywki, które można zadrukować z obydwu stron. Używając naszej nowoczesnej drukarki HiQ-MACH4.3 w prosty a przede wszystkim wyraźny (300 dpi) sposób wydrukujesz na nich instrukcje prania oraz inne informacje.

Care label 3 - Bardzo mocna tafta

To mocniejsza wersja care label, która dedykowana jest na odzież roboczą i inne tekstylia, które poddawane są praniu przemysłowemu. Mamy tu na myśli kombinezony, zasłony a nawet koce dla koni. Ten rodzaj wszywek to również rozwiązanie dla prania chemicznego. Nawet po wielokrotnym praniu, nadruk na care label 3 zachowuje swoją wysoką jakość. Ten rodzaj wszywki może być zadrukowany tylko z jednej strony przy pomocy drukarek Thermopatch z serii HiQ oraz przy wykorzystaniu taśmy barwiącej G7.

Wszystkie wszywki dostępne są w kolorze białym, w rolkach o szerokości: 30,40 lub 50 mm i długości 100 m (gilza 50 mm). Inne szerokości i/lub kolory dostępne są w zależności od nakładu na zamówienie.

Carelable tapes

Description

- CL-01: optical white polyamide taffeta, non-fray. Both sides coated. Suitable for hotfoil, flexo and thermal transfer printing on both sides, tear resistant
- CL-01 FR: optical white polyamide taffeta, non-fray. Both sides coated. Suitable for hotfoil, flexo and thermal transfer printing on both sides, tear resistant and with additional flame retardant properties
- CL-03: extra durable polyester cotton with a thermal transfer printable topcoat from polyurethane, non-fray, tear resistant

Application

Sewable labels, safety belt labels, identification labels with barcodes.
Print with suitable inks to obtain an acceptable washability.

Properties

- CL-01 and CL-01 FR: wash: 60 °C domestic
 - Dry cleaning: yes
- CL-03: wash: 90 °C domestic

- Dry cleaning: yes
- Additional FR properties for CL-01 FR: Flame retardant, cf US standard FMVSS 302 and Japanese standard JISD 1201. Aviation authority CAA no. 8 issue 2.

Limitations of use

None, when washing instructions of the underlying textile are followed.

Physical properties

- Fabric: polyester or polyamide taffeta, non fray, 76 g/m² for CL-01
- Fabric: polyester cotton, 100 g/m² for CL-03
- Colour: White
- For CL-03 an additional thermal transfer printable layer of white polyurethane is added onto the polyester cotton textile.

Before sealing

N/A

Heat seal advice

N/A

Storage and shelf life

The shelf life of this product is advised to be best before 12 months in original packing, in optimal storage.

Store at 18 – 23 °C, 50-55% RH, avoid UV exposure, store away from direct sunlight.

Health and safety precautions

No specific safety measures are required when working with this product.

Exposure controls / personal protection

Technical measures: N/A

Hazards identification

The product has not been subjected to classification following the European legislation. Special hazards designation for humans and environment: Not applicable.

Disclaimer

This information is based on the current state of our knowledge. It is however, no guarantee of

product features and no contractual relationship.

Recommended restrictions apply

This product should not be used for purposes other than specified.

Application

This data sheet has been issued by the quality control department.