Flame retardant

使用 Thermopatch 的可靠阻燃解决方案，全面提升您的工作服，确保最强的保护和卓越的耐用性。

Ready FR & ReadyPly FR
Thermopatch 专为消防制服而设计的 Ready FR 和 ReadyPly FR 徽章，具备卓越的耐热性□ReadyPly FR 配有自粘层，便于快速定位。两款徽章均可根据需求定制形状和颜色，并严格遵循 EN 469 标准。**点击这里**了解更多关于 Ready 产品的信息。

Truflex FR
Truflex FR 是广受欢迎的 Truflex 转印的阻燃版，具有更高的安全性，采用了改良的粘合剂和生产工艺。经过独立测试和认证□Truflex FR 能耐高达 60°C 的洗涤，支持几乎任何 PMS 颜色，高亮度颜色，以及精细可见的设计。最低起订量为 25 个/设计。如需了解更多关于 Truflex 产品的信息，**请点击这里**□


请查看本页面蓝色的“ 证书 ”标签，获取超过十种不同纺织品的测试报告。

Textra FR□阻燃版）
Textra FR 专为对阻燃性能有严格要求的工作服而设计，满足安全防护类服装的行业标准。在确保阻燃性能的同时，依旧提供高品质的图案效果与细节还原，适用于各类技术性纺织面料。其出色的耐用性与附着性能，使其在严苛工作环境下依旧稳定，兼具安全性与专业性。如需了解更多关于 Textra 产品的信息，请点击这里□

HiQ FR
HiQ FR 是需要严格阻燃性能的工作服的最佳选择。它符合 ISO 标准□EN ISO 11611: 2015 和 EN ISO 11612: 2015□□提供连续胶带卷和预切的标签，确保在严酷环境下仍能保持卓越性能。如需了解更多 HiQ 产品的信息，**请点击这里**□

Reflective Tape
在光线不足的环境中提升可见性和安全性，可选择 Thermopatch 的反光胶带。我们的反光带和阻燃反光带，专为需要额外保护和增强可见性的工作服设计，且提供了两种尺寸供选择。如需了解更多关于反光胶带的信息，**请点击这里**□


Plotter Transfers FR
Thermopatch 的银色热转印，非常适合低能见度的工作环境。这些反光阻燃转印符合 EN ISO 20471 标准，是需要额外安全保护的理想选择。如需了解更多关于反光徽章和银色热转印的信息，**请点击这里**□


Ready FR	
ReadyPly FR	

For more detailed press instructions for Ready and ReadyPly FR on various fabrics, click here.

Truflex FR	

For more detailed press instructions for Truflex on various fabrics, click here.

HiQ-FR	

Reflective tape	

Plotter transfers FR	

Scroll down for other FR-products.

Ready FR emblems (up to 95 °C laundry wash)			
Type of fabric	**Temp. °C**	**Pressing time in sec.**	**Pressure in Bar Low/Medium/High**
Fleece, 100% Polyester	–	–	–
Polyurethane or PVC coated polyester (rainwear), cover with baking paper	–	–	–
Knitted fabrics, 100% polyester, viscose, acrylic (Sportswear, light workwear)	–	–	–
Knitted fabrics, 100% wool, cotton (Sportswear, light workwear)	185 – 195	15	4-5 (Medium/High)

Knitted fabrics, cotton or polyester with elastane 98%/2%	–	–	–
Flame-retardant cotton or polyester cotton (FR treated, Proban®)	185 – 195	15	4-6 (Medium/High)
Cotton/polyamide 55%/45%	Preheat 195	10 15	4-6 (Medium/High)
Cotton/polyester 65%/35% or 60%/40% (with DWR finish)*	195	15	4-6 (Medium/High)
Aramid/Viscose 50%/50%	185	15	4-6 (Medium/High)
Linen, 100%	195	15	4-6 (Medium/High)
Aramid (Nomex III), 100%	185	15	4-6 (Medium/High)
Polyamide (Nylon), 100% (with DWR finish)*	185	15	4-6 (Medium/High)
Polyester 100% (with DWR finish)*	185	15	4-6 (Medium/High)
Polyester Cleanroom material anti-static 99%/1%	–	–	–

ReadyPly FR emblems (up to 95 °C laundry wash)			
Type of fabric	**Temp. °C**	**Pressing time in sec.**	**Pressure in Bar Low/Medium/High**
Fleece, 100% Polyester	–	–	–

Polyurethane or PVC coated polyester (rainwear), cover with baking paper	–	–	–
Knitted fabrics, 100% polyester, viscose, acrylic (Sportswear, light workwear)	–	–	–
Knitted fabrics, 100% wool, cotton (Sportswear, light workwear)	185 – 195	15	4-5 (Medium/High)
Knitted fabrics, cotton or polyester with elastane 98%/2%	–	–	–
Flame-retardant cotton or polyester cotton (FR treated, Proban®)	185 – 195	15	4-6 (Medium/High)
Cotton/polyamide 55%/45%	Preheat 195	10 15	4-6 (Medium/High)
Cotton/polyester 65%/35% or 60%/40% (with DWR finish)*	195	15	4-6 (Medium/High)
Aramid/Viscose 50%/50%	185	15	4-6 (Medium/High)
Linen, 100%	195	15	4-6 (Medium/High)
Aramid (Nomex III), 100%	185	15	4-6 (Medium/High)
Polyamide (Nylon), 100% (with DWR finish)*	–	–	–
Polyester 100% (with DWR finish)*	–	–	–
Polyester Cleanroom material anti-static 99%/1%	–	–	–

**DWR finish: Durable Water Repellent finish, meaning a water (dirt, oil) repellent coating on textiles based on silicone, nanotechnology, wax, and fluorocarbon.*
FR: Flame Retardant

Disclaimer
No rights can be derived from the instructions or data provided online. The information is intended for general guidance only and is subject to change without notice. We do not guarantee the accuracy, completeness, or reliability of the information provided. Users are advised to verify any information before acting on it. We accept no liability for any damage incurred because of relying on this information.