

Ready Emblems

选择 Ready Emblems 体验快速、高质量的品牌解决方案。我们提供多种产品，满足您的各种需求！

Ready & ReadyPly

如果您正在寻找能够完美展示公司或客户品牌的热封徽章 Ready Emblems 是您的最佳选择。这些徽章不仅交货迅速，还可以定制成各种形状和颜色，甚至可以精确呈现详细的照片图像。

除了广受欢迎的 Ready 我们还提供 ReadyPly 它配有便捷的自粘层。自粘层使得在纺织品上的定位变得简便快捷，确保对严格要求的场景中实现精准贴合。

无论是 Ready 还是 ReadyPly 都经过精心设计，具有耐用性，能够承受工业洗涤并保持优质效果。设计确认后，我们将在 7 个工作日内发货，徽章可以根据需求定制成各种形状和颜色，使用 Pantone 系统确保品牌色彩精准。

Ready Plus

需要在工作服或工装上遮盖旧标志吗 Ready Plus 是完美的解决方案，无需更换服装即可实现焕新工服 Ready Plus 可以覆盖几乎所有的热封标志或转印，并提供生动的全彩色设计。此外，它耐工业洗涤，确保长期耐用。无论是公司更新制服的标志还是品牌 Ready Plus 都能以经济实惠的方式保持服装的使用寿命。

Ready Stitch

Ready Stitch 是专门的缝制徽标，无需使用粘合剂，提供灵活的解决方案。这一独特的设计使徽章易于拆卸和更换，让您可以轻松更新设计。

凭借先进的数字印刷技术 Ready Stitch 能够呈现高质量的图像和清晰的细节。如果您喜欢刺绣效果，我们的创新印刷技术可以模拟刺绣的外观，包括刺绣边缘。此外，这些徽章非常耐用，且能够抵挡工业清洗的挑战。

Ready Stitch 徽章提供丰富的颜色选择，并且通过了 Oeko-Tex 认证，是企业寻求耐用且可定制徽标的理想之选。选择 Ready Stitch 尽享完美的风格、灵活性和可靠性。

Ready FR & ReadyPly FR


由 Thermopatch 专门开发的 Ready FR 和 ReadyPly FR 徽章具有卓越的阻燃性能，特别适合用于防火工作服 ReadyPly FR 还配备了自粘层，便于准确定位。两款徽章均可定制任何形状和颜色，并完全符合 EN 469 标准。欲了解更多信息，[请点击这里](#)

Ready				
ReadyPly				

For more detailed sealing instructions for Ready and ReadyPly on various fabrics, click [here](#).



Ready Plus



For more detailed sealing instructions for Ready Plus on various fabrics, click [here](#).

Ready
Stitch



Scroll down for more Ready products.

Ready and Ready FR emblems (up to 95 °C laundry wash)			
Type of fabric	Temp. °C	Pressing time in sec.	Pressure in Bar Low/Medium/High
Fleece, 100% Polyester	-	-	-
Polyurethane or PVC coated polyester (rainwear), cover with baking paper	-	-	-
Knitted fabrics, 100% polyester, viscose, acrylic (Sportswear, light workwear)	-	-	-
Knitted fabrics, 100% wool, cotton (Sportswear, light workwear)	185 - 195	15	4-5 (Medium/High)
Knitted fabrics, cotton or polyester with elastane 98%/2%	-	-	-
Flame-retardant cotton or polyester cotton (FR treated, Proban®)	185 - 195	15	4-6 (Medium/High)
Cotton/polyamide 55%/45%	Preheat 195	10 15	4-6 (Medium/High)
Cotton/polyester 65%/35% or 60%/40% (with DWR finish)*	195	15	4-6 (Medium/High)
Aramid/Viscose 50%/50%	185	15	4-6 (Medium/High)
Linen, 100%	195	15	4-6 (Medium/High)
Aramid (Nomex III), 100%	185	15	4-6 (Medium/High)
Polyamide (Nylon), 100% (with DWR finish)*	185	15	4-6 (Medium/High)
Polyester 100% (with DWR finish)*	185	15	4-6 (Medium/High)

Polyester Cleanroom material anti-static
99%/1%

-

-

-

ReadyPly and ReadyPly FR emblems (up to 95 °C laundry wash)

Type of fabric	Temp. °C	Pressing time in sec.	Pressure in Bar Low/Medium/High
Fleece, 100% Polyester	-	-	-
Polyurethane or PVC coated polyester (rainwear), cover with baking paper	-	-	-
Knitted fabrics, 100% polyester, viscose, acrylic (Sportswear, light workwear)	-	-	-
Knitted fabrics, 100% wool, cotton (Sportswear, light workwear)	185 - 195	15	4-5 (Medium/High)
Knitted fabrics, cotton or polyester with elastane 98%/2%	-	-	-
Flame-retardant cotton or polyester cotton (FR treated, Proban®)	185 - 195	15	4-6 (Medium/High)
Cotton/polyamide 55%/45%	Preheat 195	10 15	4-6 (Medium/High)
Cotton/polyester 65%/35% or 60%/40% (with DWR finish)*	195	15	4-6 (Medium/High)
Aramid/Viscose 50%/50%	185	15	4-6 (Medium/High)
Linen, 100%	195	15	4-6 (Medium/High)

Aramid (Nomex III), 100%	185	15	4-6 (Medium/High)
Polyamide (Nylon), 100% (with DWR finish)*	-	-	-
Polyester 100% (with DWR finish)*	-	-	-
Polyester Cleanroom material anti-static 99%/1%	-	-	-

Ready Plus emblems (especially for covering, up to 95 °C laundry wash)			
Type of fabric	Temp. °C	Pressing time in sec.	Pressure in Bar Low/Medium/High
Fleece, 100% Polyester	-	-	-
Polyurethane or PVC coated polyester (rainwear), cover with baking paper	-	-	-
Knitted fabrics, 100% polyester, viscose, acrylic (Sportswear, light workwear)	-	-	-
Knitted fabrics, 100% wool, cotton (Sportswear, light workwear)	-	-	-
Knitted fabrics, cotton or polyester with elastane 98%/2%	-	-	-
Flame-retardant cotton or polyester cotton (FR treated, Proban®)	195 - 204	18	4.5 (Medium/High)

Cotton/polyamide 55%/45%	195 - 204	18	4.5 (Medium/High)
Cotton/polyester 65%/35% or 60%/40% (with DWR finish)*	195 - 204	18	4-6 (Medium/High)
Aramid/Viscose 50%/50%	195 - 204	18	4.5 (Medium/High)
Linen, 100%	195	18	4.5 (Medium/High)
Aramid (Nomex III), 100%	195 - 204	18	4.5 (Medium/High)
Polyamide (Nylon), 100% (with DWR finish)*	195 - 204	18	4.5 (Medium/High)
Polyester 100% (with DWR finish)*	195 - 204	18	4.5 (Medium/High)
Polyester Cleanroom material anti-static 99%/1%	195 - 204	18	4.5 (Medium/High)

**DWR finish: Durable Water Repellent finish, meaning a water (dirt, oil) repellent coating on textiles based on silicone, nanotechnology, wax, and fluorocarbon.*

FR: Flame Retardant

Disclaimer

No rights can be derived from the instructions or data provided online. The information is intended for general guidance only and is subject to change without notice. We do not guarantee the accuracy, completeness, or reliability of the information provided. Users are advised to verify any information before acting on it. We accept no liability for any damage incurred because of relying on this information.